ALUCOOL G12+



COOLANT

A "long life" OAT (Organic Additives Technology) automotive coolant based on monoethyleneglycol and demineralized water (50%) with addition of additives to obtain the following properties:
- a perfect protection of all types of metals that are used in engines and cooling systems
- a neutral behaviour towards seals, gaskets and hoses
- a very good resistance against formation of foam
- nitrite, amine, phosphate and silicate free

APPLICATIONS

This coolant may be used all the year round in the cooling systems of gasoline and diesel engines. This coolant is ready for use and protects against freezing down to -35 °C.

PERFORMANCE LEVEL

- Ford WSS-M97B44-D
- Volkswagen VW TL 774-F ("G12 Plus")
- MB 326.3
- MAN 324 Typ SNF
- Detroit Diesel
- DAF 74002
- GM 6277M
- Leyland Trucks LTS 22 AF 10
- Renault 41-01-001/-S Type D
- Scania TB 1451
- Cummins 85T8-2
- Chrysler MS 9176
- Volvo VCS
- Mack 014GS 17004
- John Deere H 24 B1 & C1

CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		1.074
Color			RED

PACKAGING



3x5L 20L 60L 210L IBC

Vroman NV • Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@ardeca.be