MATIC 9

AUTOMATIC TRANSMISSION FLUID



A very high graded, extremely low-viscosity automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:

- excellent contribution to fuel economy
- excellent lubrication
- very good resistance against oxidation
- very good thermal stability
- excellent and very stable friction characteristics
- excellent resistance against corrosion and foaming
- excellent protection against wear
- a very high and stable viscosity index

APPLICATIONS

This premium synthetic product is specially formulated for the lubrication of certain Mercedes-Benz automatic transmissions with 9 gears. This oil contributes significantly to realizing fuel saving and can be used in automatic transmissions where an oil with the specification MB 236.17 is prescribed

PERFORMANCE LEVEL

- MB 236.17

CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		0.835
Viscosity 40 °C	mm^2/s		17.10
Viscosity 100 °C	mm^2/s		4.23
Viscosity Index			161
Flash Point COC	°C		190
Pour Point	°C		-54

PACKAGING



12x1L 4x4L 3x5L 20L 60L 210L IBC

Vroman NV • Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@ardeca.be