SYNTH-EF 5W30



SYNTHETIC MOTOR OIL

This is a full synthetic lubricant based on carefully selected very high quality base oils. This is a "LOW SAPS" oil for gasoline/LPG and diesel engines of passenger cars with or without turbo, requiring the lowest level of sulphated ash, phosphorus and sulfur and providing fuel economy.

APPLICATIONS

This oil is specifically designed for the newest generation (Euro 4) gasoline and diesel engines with diesel particulate filters (DPF), which require a low HTHS viscosity oil. It procures a significant improvement in fuel economy. This engine oil can also be used, where ILSAC GF-4 oils are recommanded.

PERFORMANCE LEVEL

- ACEA: C1
- JAGUAR / LAND ROVER STJR.03.5005

FEATURES

Aftertreatment protection : full aftertreatment system protection.
Total engine protection : outstanding engine cleanliness and durability.
Fuel economy : lower fuel consumption and CO2 emissions.

CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		0.847
Viscosity -30 °C	mPas		3900
Viscosity 40 °C	mm^2/s		52.50
Viscosity 100 °C	mm^2/s		9.46
Viscosity Index			166
Flash Point COC	°C		224
Pour Point	°C		-39
Total Base Number	mgKOH/g		6.6
Sulphate Ash	%		0.45

PACKAGING



Vroman NV • Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@ardeca.be