UNI-GEAR S 75W90



SYNTHETIC GEAR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils, which can be used in a wide field of applications. Because of its special composition, it is particularly suited for synchronized gear boxes, as well as heavily loaded differentials.

APPLICATIONS

This oil is recommended for all components of mechanical transmissions (gear boxes, transfer boxes, differentials, etc.). of trucks and four-wheel drive vehicles.

PERFORMANCE LEVEL

- API: GL-4
- API: GL-5
- API: MT-1
- DAF: GL5
- IVECO: VOITH 3.325-340
- MACK: GO-J EO-H
- MAN: 341 E-3
- MAN: 341 Z-2
- MAN: 342 M-3
- MAN: 3343-SL
- MAN: 342 S1
- MAN: 342 SL
- MB: 235.6/235.8
- MIL: PRF-2105E
- RENAULT: B0032/3 Annex 3
- SAE: J 2360
- SCANIA: STO 1
- ZF: TE-ML 02B
- ZF: TE-ML 05B
- ZF: TE-ML 07A
- ZF: TE-ML 08
- ZF: TE-ML 12B
- ZF: TE-ML 12L
- ZF: TE-ML 12N
- ZF: TE-ML 16F
- ZF: TE-ML 17B
- ZF: TE-ML 19C
- ZF: TE-ML 21B
- TMS 6816
- DIN 51517

FEATURES

Frictional properties : very smooth gear shifting, no vibration.
Anti-wear and oxidation stability : superior protection of critical parts.
Extended oil life : excellent thermal and oxidation stability.

CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		0.869
Viscosity 40 °C	mm^2/s		101.00
Viscosity 100 °C	mm^2/s		15.40
Viscosity Index			150
Flash Point COC	°C		218
Pour Point	°C		-40
Total Base Number	mgKOH/g		2.1

PACKAGING



Vroman NV • Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@ardeca.be