CERA-MIX XL 5W30



HIGH-END UNIQUE CERAMIC OIL

This ceramic synthetic 5W30 oil ready for use forms a unique composition which outperforms the properties of similar oils. The ceramic components make sure that high temperatures and pressure are resisted inside the engine. Also a low friction and wear coefficient is typical for this oil. The advantages of using the ceramic oils are summarized below:

- Significant lower fuel and oil consumption
- Increase of power
- Reduction of engine noise and internal friction
- Cleaner engine
- Improved cold start

APPLICATIONS

This advanced composition makes the oil suitable for modern and older engines, for both gasoline and diesel vehicles, often in racing applications.

PERFORMANCE LEVEL

- ACEA C3
- API SN
- BMW LL-04
- MB 229.51
- MB 229.31
- VW 502 00
- VW 505 00
- VW 505 01

CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		0.851
Viscosity -30 °C	mPas		5540
Viscosity 40 °C	mm^2/s		68.90
Viscosity 100 °C	mm^2/s		12.10
Viscosity Index			175
Flash Point COC	°C		228
Pour Point	°C		-39
Total Base Number	mgKOH/g		7.1

PACKAGING



12x1L 20L IBC

Vroman NV • Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@ardeca.be