H-EP GEAR 85W140



MINERAL GEAR OIL.

This is an extreme-pressure lubricant for gear boxes, specifically formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.

APPLICATIONS

Recommended for all hypoid transmissions and also suitable for spiral bevel gears, worm wheels and most transaxles.

PERFORMANCE LEVEL

- API: GL-5
- MIL: MIL-L-2105 C
- MIL: MIL-L-2105 D
- ZF: TE-ML 05A
- ZF: TE-ML 07A
- ZF: TE-ML 12E
- ZF: TE-ML 16B
- ZF: TE-ML 16C
- ZF: TE-ML 16D
- ZF: TE-ML 17B
- ZF: TE-ML 19B

FEATURES

Frictional properties : easy gear shifting.
Anti-wear protection : long transmission life.

CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		0.903
Viscosity 40 °C	mm^2/s		356.80
Viscosity 100 °C	mm^2/s		25.70
Viscosity Index			95
Flash Point COC	°C		224
Pour Point	°C		-15

PACKAGING



Vroman NV • Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@ardeca.be