MATIC+ IIIH



MINERAL ATF OIL.

This is a mineral lubricant based on carefully selected highly refined base oils. This is an oil with a very high viscosity index for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.

APPLICATIONS

This oil is used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements.

PERFORMANCE LEVEL

- Dexron IID/IIE/IIIF/IIIG/IIIH
- MB 236.1/236.5/236.6/236.7/236.9
- Ford Mercon/M2C138-CJ/166-H
- MAN 339 Typ Z1/V1
- Allison C4/TES-389
- Cat TO-2
- Voith 55.6335 (G607)
- Volvo 97341
- ZF TE-ML 02F/03D/04D/09A/09B/11A/11B/14A/17C

FEATURES

Frictional properties : smooth shift performance.
Anti-wear protection : extended transmission life.
Extended oil life : excellent thermal and oxidation stability.

CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		0.855
Viscosity 40 °C	mm^2/s		33.9
Viscosity 100 °C	mm^2/s		7.1
Viscosity Index			179
Flash Point COC	°C		196
Pour Point	°C		-45
Brookfield viscosity at -40 °C	mPas		17500
Color			RED

PACKAGING



12x1L 4x4L 3x5L 20L 60L 210L IBC

Vroman NV • Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@ardeca.be