MATIC MB 15



SYNTHETIC ATF

This is a full synthetic lubricant based on carefully selected very high quality base oils, intended for the latest MB 7-speed automatic transmissions from MB (NAG2FE+). It provides excellent frictional durability, superior performance and fuel economy.

APPLICATIONS

This product is recommended for sports vehicles (NAG2FE+) and is not backwards compatible with the previous 5- and 7- speed transmissions , which require MB 236.10, 236.12, 236.14.

PERFORMANCE LEVEL

- MB: 236.15

FEATURES

Anti-wear protection : significantly extended transmission life.
Frictional properties : very smooth gear shifting, no vibration.
Extended oil life : excellent thermal and oxidation stability

CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l	ASTM D4052	0.842
Viscosity 40 °C	mm^2/s	ASTM D455	17.3
Viscosity 100 °C	mm^2/s	ASTM D455	4.4
Viscosity Index		ASTL D2270	172
Flash Point COC	°C	ASTM D92	178
Pour Point	°C		-54
Brookfield viscosity at -40 °C	mPas	ASTM D2983	3500

PACKAGING



12x1L 20L 60L 210L IBC

Vroman NV • Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@ardeca.be