MATIC S-41



UNIVERSAL SYNTHETIC ATF

Synthetic all-round low viscosity Automatic Transmission oil

Is a synthetic automatic transmission oil, which has been especially developed for automatic gear boxes requiring low viscosity ATF. ensures easy shifting under all operating temperatures, without unnecessary friction. Because of the low pour point and the high VI, can be applied in a wide temperature range.Because of the excellent oxidation and thermal stability, keeps its unique properties, so it easily meets the prescribed drain intervals. A unique combination of synthetic base oils and state-of-the-art additives, guarantee all-round, easy shifting. The low viscosity ensures a fuel economy benefit compared to conventional viscosity ATF's.

APPLICATIONS

Mainly intended for the 6 or 8 speed automatic transmissions from ZF or other manufacturers, as fitted in BMW, Jaguar and Land Rover, it is also suitable for other OEMs, who recommend this type of fluid like Mercedes Benz, Hyundai, Toyota. This transmission oil is very universal in use.

PERFORMANCE LEVEL

- BENTLEY:PY112995PA
- BMW: 8322 2152426
- BMW: 8322 0144137
- BMW: M-1375.4 (8322 0142516)
- HYUNDAI: 040000C90SG
- MERCEDES BENZ 236.12
- MERCEDES BENZ 236.14
- MERCEDES BENZ 236.41
- Mitsubishi SP-IV & ATF J-2
- NISSAN MATIC - S
- SAAB 93 165 147
- TOYOTA WS
- JWS 3324
- GM DEXRON VI
- JAGUAR: Fluid 8432
- FORD MERCON LV & SP
- LAND ROVER: TYK500050
- MASERATI: 231603
- VW: G 055 005 A1/A2/A6
- VW: G 060 162 A2
- MAZDA FZ
- HONDA DW-1
- KIA / HYUNDAI SP-IV/ SPH-IV
- ZF Lifeguard Fluid 6 (S671 090 255)
- ZF Lifeguard Fluid 8

FEATURES

Anti-wear protection : significantly extended transmission life.
Frictional properties : very smooth gear shifting, no vibration.
Extended oil life : excellent thermal and oxidation stability.

CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l	ASTM D4052	0.845
Viscosity 40 °C	mm^2/s	ASTM D455	31.0
Viscosity 100 °C	mm^2/s	ASTM D445	6.2
Viscosity Index		ASTM D2270	153
Flash Point COC	°C	ASTM D2983	210
Pour Point	°C		-48
Brookfield viscosity at -40 °C	mPas	ASTM D2983	9500
Color		VISUAL	AMBER

PACKAGING



12x1L 20L 60L 210L IBC

Vroman NV • Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@ardeca.be