MOTO-TEC RACING 20W50



ESTER BASED SYNTHETIC MOTORCYCLE OIL.

A new generation synthetic engine oil for four-stroke motorcycles formulated with synthetic base oils combined with special developed balanced additives to achieve the following properties:
- a high and stable viscosity index
- optimal friction characteristics
- a very strong protection against wear, corrosion and foaming
- a very good detergency and dispersion

APPLICATIONS

This oil is special developed for the lubrication of four-stroke motorcycles, so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and tested in co-operation with the most important motorcycle producers and has its performance demonstrated in the field.

PERFORMANCE LEVEL

- JASO MA - MA2
- API: SL

CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		0.851
Viscosity 40 °C	mm^2/s		130.20
Viscosity 100 °C	mm^2/s		19.60
Viscosity Index			172
Flash Point COC	°C		236
Pour Point	°C		-51
Total Base Number	mgKOH/g		7.9
Viscosity -15 °C	mPas		1490

PACKAGING



Vroman NV • Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@ardeca.be