MULTI-TEC SN 20W50



MINERAL OIL.

A very high quality mineral engine oil, which is suitable for most of 4-stroke gasoline and diesel cars and light trucks. By its selected composition, a very good resistance to oxidation and optimal detergent and dispersion properties are obtained. A strong oil film guarantees a high lubricating power.

APPLICATIONS

This oil can be applied in modern 4-stroke gasoline (multi valves, turbo, etc.) and 4-stroke diesel engines, with or without turbo.

PERFORMANCE LEVEL

- ACEA: A3/B3
- ACEA: A3/B4
- API: SN/CF
- MB: 229.1

FEATURES

Total engine protection : engine protection and cleanliness.

CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		0.885
Viscosity 40 °C	mm^2/s		151.00
Viscosity 100 °C	mm^2/s		17.50
Viscosity Index			125
Flash Point COC	°C		238
Pour Point	°C		-24
Total Base Number	mgKOH/g		10.2
Sulphate Ash	%		1.29
Viscosity -15 °C	mPas		8000

PACKAGING



12x1L 4x4L 3x5L 20L 60L 210L IBC

Vroman NV • Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@ardeca.be