SYNTH-SX 0W40



FULLY SYNTHETIC HIGH PERFORMANCE MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils of the latest generation, with a large field of application. It offers an excellent fluidity at low temperature, which ensures instant lubrication after starting. This will bring wear to a minimum. Because of its low viscosity, it is fuel-saving.

APPLICATIONS

All 4-stroke gasoline engines, four-valve, turbocharged, and 4-stroke diesel engines with or without turbo. This oil is not suitable for diesel particulate filters.

PERFORMANCE LEVEL

- ACEA: A3/B4
- API: SN
- BMW: LONGLIFE-01
- MB: 229.5
- PORSCHE: A40
- RENAULT: RN 0700
- RENAULT: RN 0710
- VW: 502 00
- VW: 505 00

FEATURES

Total engine protection : performance in keeping the engine clean.
Fuel economy : superior fuel economy and CO2 reduction.
Cold start : excellent fluidity at low temperature.

CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		0.846
Viscosity 40 °C	mm^2/s		83.70
Viscosity 100 °C	mm^2/s		14.00
Viscosity Index			173
Flash Point COC	°C		232
Pour Point	°C		-46
Total Base Number	mgKOH/g		10.5
Sulphate Ash	%		1.33
Viscosity -35 °C	mPas		6000

PACKAGING



Vroman NV • Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@ardeca.be