SYNTH-SX 5W40



SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils and high quality additives of the latest generation, specially designed to meet the strict requirements of manufacturers. This provides an excellent fluidity at low temperatures, a very low resistance when starting, an exceptional viscosity index and a very high thermal stability.

APPLICATIONS

This oil is used in gasoline engines of cars, which demand the highest performance and diesel engines of passenger cars with turbo and direct fuel injection. The high quality allows extended drain intervals, according to the specific requirements of manufacturers.

PERFORMANCE LEVEL

- ACEA: A3/B4
- API: SN/CF
- BMW: LONGLIFE-01
- MB: 226.5
- MB: 229.3
- OPEL: GM-LL-B-025
- Fiat 9.55535-M2
- PORSCHE: A40
- PSA: B71 2296
- RENAULT: RN 0700
- RENAULT: RN 0710
- VW: 502 00
- VW: 505 00

FEATURES

Total engine protection : performance in keeping the engine clean.
Cold start : excellent fluidity at low temperature.
Drain interval extension : longer oil drain interval.

CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		0.853
Viscosity -30 °C	mPas		5740
Viscosity 40 °C	mm^2/s		90.2
Viscosity 100 °C	mm^2/s		15
Viscosity Index			175
Flash Point COC	°C		223
Pour Point	°C		-42
Total Base Number	mgKOH/g		10.5
Sulphate Ash	%		1.33

PACKAGING



12x1L 4x4L 3x5L 20L 60L 210L IBC

Vroman NV • Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@ardeca.be