UNI-GEAR LS 75W140



SYNTHETIC GEAR OIL.

This is a fully synthetic lubricant based on carefully selected highly refined base oils. This is a high performance transmission oil for all differentials, including those equipped with a "limited slip" mechanism. It is characterized by an exceptionally high viscosity stability at different temperatures and a very high fluidity at low temperature.

APPLICATIONS

This product is used in highly loaded axles and reduction gears of cars, trucks and off-road equipment. It has "limited-slip" characteristics, and is specifically recommended for 4X4 vehicles.

PERFORMANCE LEVEL

- API: GL 4+, GL-5 / LS
- MIL: MIL-L-2105 E
- BMW MSP/A
- SCANIA STO 1.0 box
- MAN 341 Z2, 341 E3, 342 M3
- MB 235.8
- ZF TE-ML 02B, 05B, 07A, 08, 12B, 16F, 17B, 19C, 21B
- IVECO axles
- VOITH 3.325-340
- Arvin Meritor O-76N
- INTERNATIONAL TMS-6816
- DAF

FEATURES

Frictional properties : very smooth gear shifting, no vibration.
Anti-wear protection : extended transmission life.
Extended oil life : excellent thermal and oxidation stability.

CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		0.905
Viscosity 40 °C	mm^2/s		170
Viscosity 100 °C	mm^2/s		26.5
Viscosity Index			195
Flash Point COC	°C		160
Pour Point	°C		-51

PACKAGING



Vroman NV • Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@ardeca.be